



120.00 mm

BLAUPUNKT



Rear of Unit



PIN	DEFINITION A PART	PIN	DEFINITION B PART
1	CAN-L	1	Rear R+
2	NC	2	Rear R-
3	CAN-H	3	Front R+
4	ACC	4	Front R-
5	NC	5	Front L+
6	NC	6	Front L-
7	BATT +12V	7	Rear L+
8	GND	8	Rear L-

DEFINITION C PART					
PIN	C1 PART	PIN	C2 PART	PIN	C3 PART
1	Video GND	7	NC	13	NC
2	NC	8	P.CONT*	14	NC
3	NC	9	NC	15	NC
4	Camera Video	10	NC	16	NC
5	NC	11	NC	17	NC
6	NC	12	NC	18	NC
---	---	---	---	19	NC
---	---	---	---	20	NC

PIN	DEFINITION
1-20	NC
21	Front L
22	Front R
23	Audio GND
24	Rear L
25	Rear R
26	Rear Video OUT 2
27	SUB OUT
28	Audio GND
29	Rear L OUT
30	Rear R OUT
31	Rear Video OUT 1
32	AUX IN Video
33	Video GND
34	AUX Audio GND
35	AUX IN L
36	AUX IN R

Warnings:
 Warranty void if this unit is damaged due to misuse or unauthorized service attempting.
 Before making any electrical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.
 Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.
 Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology. Help keep the world clean! Dispose properly!



CE 2200



10R-032588

FCC ID: RPL-PHL835

Remarks: (*) Total max. 150 mA / Fuse: 15 Ampere
 12V ⊖ GROUND --- 15A max

P/N:127071003319

100.00 mm